



Silicone Spray FLC 710

ELKALUB FLC 710 is a low-viscosity lubricant glidant (approx. 37 mm²/s at 40 °C) is a product which is well suited for intermediate spraying during running production or for a very thin film. This film evaporates quickly. The product is mainly applied for paper and cardboard but can also be used for wood, rubber, plastics and on metal surfaces. Spray filling with: light hydrocarbons, butane.

□□ □□

□□□□ -50 °C bis 170 °C

40°C □□□□ (□□□□) 37 mm²/s

□□

- □□□□-□□□□
- □□□□□□

□□

- □□
- □□□□
- □□
- □□□□
- □□□□

□□

- □□□/□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

□□

- 400□□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com