



silicone Spray FLC 745 H1 Halal



ELKALUB FLC 745 is a medium-viscous glidant (approx. 260 mm²/s at 40 °C) USDA H1 approved (Registration No. 126160) The transparent, non-smelling lubricating film protects and conserves the surface. The product is mainly used in food industries or in printing plants for food packaging. It is suited for foils and plastics (e.g. conveyors) as well as for rubber (e.g. rollers), paper and on metal surfaces. Spray filling with: light hydrocarbons, butane. Registration no. (H1): 126160

□□ □□

□□□□ -50 °C bis 170 °C

40°C □□□□ (□□□□) 260 mm²/s

□□

- □□□□O-□□□□□□
- □□□□□□□□

□□

- □□
- □□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
- □□□□□
- □□□□

□□

- □□
- □□□/□□□
- □□□□

□□

- 400□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com