



KP2K-20

Special grease GLS 135/N2

ELKALUB GLS 135/N2 is a lithium-saponified, water resistant and corrosion inhibiting universal grease. It can be used for roller and slide bearings in the temperature range from -20 °C to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of linear guidance systems as well as for ball bearings up to a speed factor ndm of 500.000. ELKALUB GLS 135/N2 has a very low oil bleeding and separation tendency. Therefore it is well conveyable in central lubricating systems (conveying test at bielomatik and Lincoln).

□□ □ □□□

□□□ □□□□□

□□ 100 mm²/s

□□□□ -20 °C bis 120 °C

NLGI □ 2

□□

- □□□□
- □□□□
- □□□□□□□□
- □□□□□□

□□

- □□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- □□
- □□□□
- □□□□

□□

- □□□

□□

- 250□□
- 100□□□
- 380□LubeShuttle
- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com