



KPHC2K-20

special-grease GLS 964/N2 H1 Halal



ELKALUB GLS 964/N2 is a lubricating grease with good wear and corrosion protection properties. It has been designed for use in roller and slide bearings, especially for permanently changing directions of movement. The integrated thixotropy permits the build-up of a more solid grease collar at the outer side of bearings. By that, the spin-off of grease and the penetration of foreign particles is reduced. Examples of application: gripper shafts, spindles, badly sealed bearings.

□□ □□

□□□ □□

□□ 150 mm²/s

□□□□ -25 °C bis 130 °C

NLGI □ 2

□□

- □□□□
- □□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

- □□
- □□
- □□
- □□□□
- □□□□
- □□□□

□□

- □□

□□

- 250□□
- 100□□□
- 380□LubeShuttle
- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com