



KPFHC2N-40

special-grease GLS 980/N2 H1 Halal



ELKALUB GLS 980/N2 is a high-quality multi-purpose grease for application in roller and slide bearings, for slipways as well as for open lubrication points. Due to its synthetic oil base the grease is very resistant to ageing and can be used in a wide temperature range (-40 °C / +140 °C). **ELKALUB GLS 980/N2** is NSF H1-approved and is therefore suited for environments with food contact.

□□ □ □α□□

□□□ □□□□ □□□□□

□□ 220 mm²/s

□□□□ -40 °C bis 140 °C

NLGI □ 2

□□

- □□□□
- □□□□
- □□□□□□
- □□□□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□
- □□
- □□□□
- □□□□
- □□□□

□□

- □□
- □□
- □□

□□

- 250□□
- 100□□□
- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com