



KP3G-15

Special adhesive grease for bearings and gears GLL 6/N3

ELKALUB GLL 6/N3 is a special grease based on mineral oil. ELKALUB GLL 6/N3 is extremely long-fibred, adhesive and resistant to pressure and centrifugal forces for temperatures from -15 °C up to +100 °C. ELKALUB GLL 6/N3 is used for the lubrication of roller bearings and gears in the low speed range (speed factor $ndm < 300.000$), for open gear wheels in eccentrics as well as for slow turning slide bearings. ELKALUB GLL 6/N3 has antinoise qualities and is water-resistant. Examples for application: Open gear wheels, points of lubrication with centrifugal losses, poorly sealed bearings.

□□ □□□

□□□ □□□□□

□□ 272 mm²/s

□□□□ -15 °C bis 100 °C

NLGI □ 3

□□

- □□□□
- □□□□
- □□□□□□
- □□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□□□
- □□□□
- □□□□□
- □□□□

□□

- □□□□□□□□

□□

- 250□□
- 400□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com