



KPHC2K-20

Synthetic grease for spindle bearings GLS 935/N2-3

ELKALUB GLS 935/N2-3 is a synthetic high performance grease which is suitable for the lubrication of fast rotating tool spindles. The grease can be used up to a speed value ($n \times dm$) of 1,800,000. The low base oil viscosity of Elkalub GLS 935/N2-3 is responsible for the equally low frictional resistance and allows the oil to flow back quickly into the track. Both lead to lower storage temperatures and thus to an extended service life of the spindle. The additive package from Elkalub GLS 935/N2-3 combines high payloads with low wear and good corrosion protection. Elkalub GLS 935/N2-3 can be stably conveyed by a lubricator (e.g. FlexxPump) and is therefore very well suited for the automated grease relubrication of high-performance spindles.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

□□ □ □α□□

□□□ □□□□□

□□ 30 mm²/s

□□□□ -20 °C bis 120 °C

NLGI □ 2 - 3

□□

- □□□□
- □□□□
- □□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□
- □□□□

□□

- □□
- □□□□
- □□□

□□

- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com