



Drip free adhesive spray FLC 804

ELKALUB FLC 804 is an oil spray based on high grade white- and synthesis oils containing high-performance additives. The lubricating film has a good spreading capability and protects against corrosion. It has excellent boundary lubrication properties and is very adhesive and resistant to centrifugation up to 80 °C. ELKALUB FLC 804 is recommended for usage in hinges, joints, heavy drive chains, cams, cam discs, open gears, guides and spindles. ELKALUB FLC 804 acts silencing. Due to the prompt evaporation of the solvent a fast and drip free application on vertical points of lubrication is possible.

□□ □□□

□□□ □□

□□□□ -20 °C bis 100 °C

40°C □□□□ (□□□□) 6000 mm²/s

□□

- □□
- □□

□□

- □□
- □□□□
- □□□□
- □□
- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□□□
- □□□□

□□

- □□□□□□□□
- □□□□

□□

- 150□□□□□□
- 400□□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com