



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP2K-20

Universal grease for bearings and gears GLL 7/N2

ELKALUB GLL 7/N2 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. ELKALUB GLL 7/N2 has a special ELKALUB-additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 up to +120° C. ELKALUB GLL 7/N2 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed index (ndm*) of about 400.000.

□□ □□□

□□□ □□□□□

□□ 97 mm²/s

□□□□ -20 °C bis 120 °C

NLGI □ 2

□□

- □□□□
- □□□□

□□

- □□
- □□□□
- □□□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□□□□□□□
- □□

□□

- 250□□
- 400□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com