



White oil LFC 3046 H1 Halal



The oils of the series ELKALUB LFC 3000 are mainly intended for application in the food and drink industry for temperatures from -10 °C (-20 °C) up to +120 °C. These oils are highly resistant to aging and free from resinification. They can be applied in situations where incidental food contact is possible. We possess a USDA H1 approval for all viscosity grades. The oils of the series ELKALUB LFC 3000 offer a good protection against corrosion and are well compatible with plastics and sealings. The products are compatible with mineral oils. ELKALUB LFC 3000 oils are mainly applied for gears and chains, as circulation oils, as well as for hydraulic and pneumatic systems.

□□ □□

□□□□ -20 °C bis 120 °C

40°C □□□□ 46 mm²/s

□□

- □□□□
- □□□□
- □□□□
- □□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
 - □□
 - □□
 - □□□□
-

□□

- □□
 - □□□□
-

□□

- 5□□□
 - 20□□
 - 200□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com